

MYERS TIRE SUPPLY  
MATERIAL SAFETY DATA SHEET

Product Name: SLIP TAC  
Product Code No.: 46-250, 46-251, 46-252

Page : 1 of 3  
Issue Date: Sep. 23, 2003

MANUFACTURER:  
  
PATCH RUBBER COMPANY  
P.O. BOX H  
ROANOKE RAPIDS, N.C. 27870  
  
TELEPHONE: (252) 536-2574

Call CHEM TEL only in the event of chemical emergencies involving a spill, leak, fire, exposure, or accident involving chemicals.  
(800) 255-3924 North America  
(813) 248-0585 (Collect) International

HEALTH EMERGENCIES:  
Call LOS ANGELES Poison Information Center  
(24 hrs.) 1-800-356-3129

PRODUCT IDENTIFICATION

PRODUCT NAME: SLIP TAC  
DOT PROPER SHIPPING NAME: N/A  
ID NUMBER: N/A  
DOT HAZARD CLASSIFICATION: N/A

SECTION I - HAZARDOUS COMPONENTS

Components	Percent	Exposure Limits	Units	Agency	Type
------------	---------	-----------------	-------	--------	------

NOT APPLICABLE

SECTION II - EMERGENCY & FIRST AID PROCEDURES \*\*\*\*\*EMERGENCY\*\*\*\*\*  
Have a physician call Los Angeles  
POISON INFORMATION CENTER (24 hrs.)  
1-800-356-3129

**EYE CONTACT:** Immediately flush eyes with plenty of 1% physiological saline for five minutes while holding eyelids open; see a physician. Salin flush is the treatment of choice. However, if no saline is easily available, flush with water for 15 minutes, then see a physician.

**SKIN CONTACT:** Wash the affected area with plenty of soap and water.

**INHALATION:** No effects requiring first aid are expected.

**INGESTION:** No effects requiring first aid are expected.

Product Name: SLIP TAC  
Product Code No.: 46-250, 46-251, 46-252

Page : 2 of 3  
Issue Date: Sep. 23, 2003

### SECTION III - HEALTH HAZARDS/ROUTES OF ENTRY

**CARCINOGENIC STATUS:** Product ingredients are not listed by IARC, NTP, or OSHA.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** None known.

**ACUTE HEALTH EFFECTS:** Product is a gelatinous liquid which may produce a gelatinous film when in contact with the eye which may be difficult to remove using only water. Irritation experienced, if any, is expected to be a physical rather than a chemical effect.

**CHRONIC MEDICAL EFFECTS:** None known.

**EFFECTS OF OVEREXPOSURE/SIGNS AND SYMPTOMS OF EXPOSURE:** No adverse health effects are expected.

### SECTION IV - SPECIAL PROTECTION INFORMATION

**VENTILATION:** Effective general ventilation recommended as a good work practice.

**RESPIRATORY PROTECTION:** Not typically required.

**PROTECTIVE EQUIPMENT:** Goggles suitable for keeping liquid out of the eyes.

### SECTION V - REACTIVITY DATA

**STABILITY:** Stable

**HAZARDOUS POLYMERIZATION:** Will not occur.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Small amounts of CO, CO<sub>2</sub>, and smoke composed of aromatic and aliphatic Hydrocarbons.

**INCOMPATIBILITY (CONDITIONS/MATERIALS TO AVOID):** Strong basic materials such as ammonia, sodium hydroxide, potassium hydroxide or strongly basic amines.

### SECTION VI - SPILL OR LEAK PROCEDURES \*\*HIGHWAY /RAILWAY SPILLS\*\*

CALL CHEM TEL 1-800-255-3924 North America  
(Collect) 1-813-248-0585 International

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Absorb onto rag or floor absorbent.

**CAUTION: SPILLED PRODUCT IS SLIPPERY**

**WASTE DISPOSAL METHOD:** Incinerate or landfill waste in accordance with federal, state, and local regulations.

Product Name: SLIP TAC  
Product Code No.: 46-250, 46-251, 46-252

Page : 3 of 3  
Issue Date: Sep. 23, 2003

**SECTION VII - STORAGE AND SPECIAL PRECAUTIONS**

**PRECAUTIONS TO BE TAKEN DURING HANDLING AND STORING:**

- Do not get in eyes.
- Wash thoroughly after handling product. Always wash up before eating, smoking, or using toilet facilities.
- Keep container closed.

**SECTION VIII - FIRE & EXPLOSION HAZARD DATA**

**FLASH POINT:** N/A

**FLAMMABLE LIMITS IN AIR:** N/A

**SPECIAL FIRE FIGHTING PROCEDURES:** Wear positive pressure self-contained breathing apparatus (SCBA). Personnel not having suitable respiratory protection must leave area to prevent significant exposure to toxic combustion gases from any source.

**SECTION IX - PHYSICAL DATA**

**APPROX. BOILING POINT:** 212°F **VAPOR DENSITY (AIR = 1):** N/A

**VAPOR PRESSURE:** N/A **EVAPORATION RATE (N-BUTYL ACETATE = 1)** N/A

**% VOLATILE:** N/A **% SOLUBILITY IN WATER:** 100

**SPECIFIC GRAVITY:** 1.01 **APPEARANCE:** Slippery blue liquid.

**ODOR:** Little, if any odor.

**SECTION X - DOCUMENTARY INFORMATION**

<b>ISSUE DATE:</b>	9/23/03	<b>PRODUCT CODE NO:</b>	46-250, 46-251, 46-252
<b>PREV. DATE:</b>	1/01/01	<b>PREV. PROD. CODE NO:</b>	46-250, 46-251, 46-252
<b>MSDS NO:</b>	0043	<b>PREV. MSDS NO:</b>	N/A

**DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES**

The information in this document is believed to be correct as of the date issued. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM HAZARDS RELATED TO ITS USE. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of his use thereof.

PREPARED BY: Marlo Carter